QUART LED Wall Light 12W IP54

Product codes:

Reference: 8221



Product features:

Power (W): 12
Power source (V): 85-265V
Color temperature CCT: 3000K
LED: SMD2835
Brightness (Lm): 1200
Color rendering index (Ra):: ?85
Colour: White
IP: IP54
Frequency (Hz): 50-60Hz
Measures (mm): 190x190x60mm
Material: Aluminum + PC
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2023: G
Lifespan: 30.000h
Certification: CE - RoHS
Warranty: 2 años

Product attributes:

Color temperature CCT (ºK): Warm white 3000K

Product description:

Adjustable square wall light, minimalist design, in./out. IP54 QUART LED Wall Light 12W White 1200 lm 3000K IP54 Adjustable

The with a square, minimalist design offers in warm white. White-lacquered aluminium and polycarbonate, it to direct the light. , 190x190x60 mm, indoor and protected outdoor.

? 12W? 1200 lm? 3000K? IP54

12W
Power1200 lm
Luminous flux3000K
Warm whiteIP54
Protection

The **QUART LED wall light** is a square, modern, elegant, minimalist wall fixture, designed to bring decorative, functional lighting to a wide variety of spaces. Thanks to its **IP54** protection rating, it suits both indoor environments and protected outdoor areas.

Made of aluminium and polycarbonate, with an excellent-quality white lacquered finish, the QUART light stands out for its ability to **tilt fully on its own axis**, allowing you to direct the light wherever you want. With 12W consumption, it offers a flux of **1200 lumens** in 3000K warm white. Dimensions 190x190x60 mm.

Why choose this product? **? Adjustable on its axis**

Full tilt to direct the light. **? 12W, 1200 lm, 3000K**

Warm white, decorative and functional lighting. **? IP54, minimalist square**
White aluminium and polycarbonate, in. and protected out. Technical specifications Product typeQUART adjustable LED wall lightPower12WLuminous flux1200 lmColour temperature3000K (warm white)MaterialAluminium and polycarbonateColourWhiteOrientationTilts on its axisProtectionIP54Dimensions190x190x60 mm Advantages

- **Adjustable:** tilts on its axis.
- **12W, 1200 lm:** 3000K warm white.
- **IP54:** indoor and protected outdoor.
- **Square design:** minimalist and elegant.
- **White aluminium + PC:** sturdy and durable.
- **190x190x60 mm:** wall format.

Recommended applications ?**Facades and entrances** — adjustable lighting.?**Living rooms and corridors** — minimalist design.?**Protected terraces** — IP54 outdoor.?**Bedrooms** — 3000K warm white. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Fix to the wall**
Screw the light's bracket to the wall.3**Wire it**
Wire it to the 230V mains.4**Aim it**

Tilt the light on its axis and check the lighting. Frequently asked questions **Is it adjustable?**

Yes, it tilts fully on its own axis. **Is it suitable for outdoors?**


Yes, its IP54 rating allows a protected outdoor installation. **What is its power?**
12W for 1200 lumens, in 3000K warm white. ?

12W
1200 lm?
3000K
IP54?
Adjustable
190x190x60?
In stock
Fast shipping

Product gallery:








19 cms
19 cms

