50W RGBW IP65 Outdoor LED Floodlight (multicolour + white) 4500Lm

Product codes:

Reference: FL50W-RGB



Product features:

Power (W): 50
Power source (V): 175-260V
Color temperature CCT: RGBW
LED: SMD2835
Dimmable: Control Remoto
Brightness (Lm): 4500
Color rendering index (Ra):: ?80
Colour: Black
IP: IP65
Frequency (Hz): 50-60Hz
Power factor ?: 0.91
Measures (mm): 226x255x40mm
Material: Aluminum + glass
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2021: A+
Lifespan: 25.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): RGBW

Product description:

Decorative RGBW floodlight, multicolour + white, outdoor Outdoor RGBW LED Floodlight 50W 4500 lm 120º IP65 with Remote

The with an SMD2835 chip offers with a wide angle. lighting (multicolour + white) with a remote, ideal for gardens, facades, terraces and events. IP65, 226x255x40 mm.

? 50W? 4500 lm? RGBW? IP65

50W
Power 4500 lm
Luminous flux 120º
Angle IP65
Protection

The **50W outdoor RGBW LED floodlight** is the perfect option for creating decorative lighting and colour effects outdoors. Fitted with a high-brightness SMD2835 LED chip, it offers a luminous flux of **4500 lumens** with a wide 120º opening angle, ideal for lighting gardens, facades, terraces and outdoor events.

Its **RGBW** lighting lets you choose between a multitude of colours and a crisp white, all easily controlled by **remote**. With an **IP65** protection rating, it resists rain and dust, ensuring reliable outdoor operation. Dimensions 226x255x40 mm.

Why choose this product? **? RGBW lighting**
Multicolour + white, colour effects by remote. **? SMD2835, 4500 lm**
Wide 120º angle, 50W, decorative and powerful. **? IP65 outdoor**
Rain- and dust-resistant, gardens and facades. Technical specifications Product type Outdoor RGBW LED floodlight Power 50W Luminous flux 4500 lm Colours RGBW (multicolour + white) LED chip SMD2835 Angle 120º Control Remote Protection IP65 Dimensions 226x255x40 mm Use Outdoor Advantages

- **RGBW:** multicolour + white.
- **50W, 4500 lm:** SMD2835.
- **120º angle:** wide opening.
- **Remote:** colour effects.
- **IP65:** outdoor, rain and dust.
- **226x255x40 mm:** decorative and powerful.

Recommended applications ? **Gardens and facades** — colour effects. ? **Terraces and patios** — decorative atmosphere. ? **Outdoor events** — dynamic RGBW. ? **Pools and trees** — highlighting. Installation guide 1 **Switch off the power**
Cut the supply before installation. 2 **Fix the floodlight**
Aim and fix the floodlight on its bracket. 3 **Wire it**
Wire it to the 230V mains. 4 **Pair the remote**
Select the RGBW colours and effects. Frequently asked questions **Can the colours be changed?**
Yes, RGBW lighting (multicolour + white) by remote. **Is it suitable for outdoors?**
Yes, its IP65 rating resists rain and dust. **What is the beam angle?**
120º, for 4500 lumens (50W). ?

50W
4500 lm ?

RGBW
120º ?

IP65
226x255x40 mm ?


In stock
Fast shipping

Product gallery:


50W
RGBW
IP65





RGBW
DIMMABLE
Remote Control



Up: brightness up/flash fast
Down: brightness down/flash slow
Power ON/OFF
R: Color change to Red
G: Color change to Green
B: Color change to Blue
W: Color change to White
Other no-letter butters: for the respective color
Modes keys: 4 classic lighting modes




IP65
50W
RGBW
IP65


Anti-Condensation Valve


Installation


226 mm
40mm
255 mm