5W 30cm Selectable CCT Undercabinet T5 LED batten

Product codes:

Reference: PLR5W



Product features:

Power (W): 5
Power source (V): 100-240V
Color temperature CCT: 6500K
LED: SMD2835
LED chip brand: SAN'AN
Brightness (Lm): 472
Color rendering index (Ra):: ?80
Colour: White
IP: IP20
Luminous angle: 120º
Frequency (Hz): 50-60Hz
Power factor ?: 0.90
Measures (mm): 295x22x34mm
Material: Aluminum + PC
Operating temperature: -20ºC ~ +40ºC
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 25.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K-6000K)

Product description:

T5 30 cm CCT batten, modular for furniture T5 LED Batten 5W 30 cm Selectable CCT 472 lm IP20 without switch

The offers with a selector (3000K / 4000K / 6500K). Compact and modular, ideal under kitchen units, shelves and countertops. IP20, linkable without switch.

? 5W? 472 lm? CCT? 30 cm

5W
Power472 lm
Luminous fluxCCT

3000-6500K30 cm
Length

The **T5 LED batten 5W, 30 cm** is a compact, modular lighting solution, perfect for installing under kitchen units, shelves, countertops and bookcases. With a luminous flux of **472 lumens** and a **CCT** selector (3000K, 4000K, 6500K), it adapts to any atmosphere.

Thin (22x34 mm) and **IP20**-rated, it integrates discreetly into any furniture and indoor space. It connects easily and can be linked with other battens. Several battens can be linked together to cover greater lengths with a single supply.

Why choose this product? **? CCT selector**
3000K, 4000K or 6500K to suit the atmosphere. **? Compact 30 cm**
472 lm, thin (22x34 mm), discreet. **? Linkable**
Several battens on a single supply. Available light shades

CCT selector: choose the colour temperature to suit the desired atmosphere.

3000 K
Warm white4000 K
Neutral white6500 K
Cool white Technical specifications Product typeT5 LED battenPower5WLuminous flux472 lmColour temperatureCCT 3000K / 4000K / 6500KLength30 cmThickness22x34 mmSwitchNoProtectionIP20UseIndoor (furniture, shelves)
Advantages

- **CCT selector:** 3000/4000/6500K.
- **5W, 472 lm:** 30 cm, compact.
- **Thin:** 22x34 mm, discreet.
- **Linkable:** on a single supply.
- **Without switch:** simple connection.
- **Furniture and shelves:** modular lighting.

Recommended applications ?**Kitchens** — under-units and worktops.?**Shelves and bookcases** — modular lighting.?**Windows and shops** — highlighting.?**Offices and cupboards** — discreet light. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Choose the temperature**
Set the CCT selector (3000/4000/6500K).3**Fix the batten**
Fix it under the unit or shelf.4**Wire and link**
Wire it (and link other battens if needed). Frequently asked questions **Can the temperature be chosen?**
Yes, CCT 3000K, 4000K or 6500K via the selector. **Can several battens be linked?**
Yes, to cover greater lengths with a single supply. **What is its length?**
30 cm, with a thickness of 22x34 mm. ?

5W
472 lm?

CCT
30 cm?

T5
Linkable?

In stock
Fast shipping

Product gallery:




INSTALACIÓN
Paso 1:
Conecte los cables a una toma de corriente 230V.
El cable amarillo corresponde a la toma de tierra
Paso 2:
Conecte el otro extremo a la regleta.


CHIP LED
SMD 2835


1
2
3
4



