42W IP54 KING Slim Recessed LED Panel 3200Lm

Product codes:

Reference: LD-KNG42060



Product features:

Power (W): 42
Power source (V): 220-240V
Color temperature CCT: 4000K
LED: SMD2835
LED chip brand: EPISTAR
Brightness (Lm): 3200
Color rendering index (Ra):: ?80
Colour: White
IP: IP54
IK: IK08
Luminous angle: 0.9
Frequency (Hz): 50-60Hz
Power factor ?: 0.9
Material: Aluminum + PC
Driver: Sí
Operating temperature: +5ºC ~ +30ºC
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 40.000h
Certification: CE - RoHS

Product attributes:

Color temperature CCT (ºK): Natural white 4000K

Product description:

KING 60x60 slim panel, IP54, professional lighting KING LED Panel 60x60 cm 42W 3200 lm IP54 Slim Recessed

The , slim recessed, offers
with uniform, efficient lighting. rating, ultra-thin design, ideal for offices,
shops and modular ceilings.

? 42W? 3200 lm? 60x60? IP54

42W
Power3200 lm
Luminous flux60x60 cm

FormatIP54
Protection

The **KING slim recessed 42W LED panel** is an efficient, modern lighting solution, with an **IP54** rating, ideal for those seeking professional, high-quality lighting. With 42W of power and a luminous flux of **3200 lumens**, it ensures clear, even lighting.

Its **ultra-thin** design in the **60x60 cm** format fits perfectly into Armstrong-type modular ceilings, false ceilings and offices. Sturdy and durable, it suits professional and residential spaces: offices, shops, meeting rooms, schools and halls.

Why choose this product? **? 60x60 slim format**
Ultra-thin design, Armstrong modular ceilings. **? 42W, 3200 lm**
Clear, even, efficient lighting. **? IP54**
Resistant, professional and residential spaces. Technical specifications Product typeKING 60x60 cm slim LED panelPower42WLuminous flux3200 lmFormat60x60 cmDesignSlim (ultra-thin)ProtectionIP54InstallationRecessed / modular ceilingsUseOffices, shops, indoor Advantages

- **60x60 cm slim:** ultra-thin design.
- **42W, 3200 lm:** even lighting.
- **IP54:** resistant.
- **Armstrong ceilings:** recessed.
- **Offices and shops:** professional.
- **Durable:** high quality.

Recommended applications ?**Offices and meeting rooms** — even lighting.?**Shops** — modular ceilings.?**Schools and hospitals** — IP54.?**Halls and corridors** — 60x60 panel. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Recess the panel**
Place the panel in the Armstrong ceiling or via a kit.3**Wire the driver**
Connect the driver and the panel.4**Check**
Restore power and check the lighting. Frequently asked questions **What is its format?**
60x60 cm slim, for modular ceilings. **What is its luminous flux?**
3200 lumens for 42W. **Is it suitable for damp areas?**
Its IP54 rating suits slightly damp rooms. ?

42W
3200 lm?

60x60
Slim?

IP54
KING?

In stock
Fast shipping

Product gallery:

