

72W 120x60cm Slim LED Panel 6500Lm UGR19

Product codes:

Reference: IL-PL72W60



Product features:

Power (W): 72

Power source (V): 100-240V Color temperature CCT: 4000K Color temperature CCT: 6000K

LED: SMD2835 Brightness (Lm): 6500

CRI: +80 Colour: White IP: IP20

Luminous angle: 120 Frequency (Hz): 50-60Hz Power factor: 0.95

Measures (mm): 1195x595x9mm

Material: Aluminum + PC

Operating temperature: -20°C ~ +55°C

Energy efficiency 2021: A+ Energy efficiency 2023: G

Lifespan: 35.000h Certification: CE - RoHS Warranty: 3 años

Product attributes:

Color temperature CCT (°K): Natural white 4000K

Product description:

The 60x120cm and 72W LED panel is a versatile and efficient lighting solution for commercial and residential spaces. With its slim and modern design, it easily integrates into suspended or recessed ceilings, providing uniform, high-quality lighting.

With a power of 72W, this LED panel emits a luminous flux of 6500 lumens, ensuring bright and suitable lighting for a wide variety of applications.

With a color rendering index (CRI) greater than 80, this LED panel displays colors accurately and naturally, enhancing the visual quality of the environment.

Furthermore, the LED panel has a lifespan of approximately 50,000 hours, which means extended durability and reduced long-term maintenance costs.

The LED panel is compatible with dimmers or compatible LED controllers, allowing light intensity to be adjusted according to user needs and preferences.

This LED panel meets CE and RoHS certifications, ensuring its quality, safety, and compliance with environmental



regulations.

Compatible Accessories (sold separately):

- TRIAC dimmable driver
- Surface mount frame
- · Recessed frame for plasterboard
- · Suspension kit
- · Recessed mounting clips

Main Features:

Panel type: LEDDimensions: 60x120cm

• Power: 72W

• Luminous flux: 6500 lumens

Color temperature: 4000K (neutral white)
Color Rendering Index (CRI): >80
Operating voltage: 220-240V AC
Lifespan: Approximately 50,000 hours

· Certifications: CE, RoHS

Additional Features:

- High energy efficiency and low power consumption
- · Instant on without flickering
- Slim and modern design
- Durable aluminum frame
- Uniform light distribution
- No ultraviolet (UV) or infrared (IR) radiation
- Free of mercury and harmful substances
- Easy installation in suspended or recessed ceilings
- Controllable with dimmable drivers or compatible LED controllers

Product gallery:

