Motion Detector mural PIR 180º 3 adjustments IP44 noir

Product codes:

Reference: CR-CR2000-10



Product features:

Power (W): Máx. 300W LED
Power source (V): 220-240V
Dimmable: Sí
Colour: Black
IP: IP44
IK: IK08
Frequency (Hz): 50-60Hz
Measures (mm): 135x66x114mm
Material: ABS
Operating temperature: -20ºC ~ +30ºC
Energy efficiency 2023: A
Lifespan: 30.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Product description:

PIR wall detector 180º, 3 settings, IP44 PIR Motion Detector Wall 180º 230V max 300W LED 3 Settings IP44 Black

The , high sensitivity, adjusts via 3 settings (range, time delay, light level). operation, max load , 5-12 m range, 10 s to 7 min delay, 3-2000 lux threshold. Black, rating.

? PIR 180º? 300W LED? 10s-7min? IP44

180º
Detection300W LED
Max load5-12 m
RangeIP44

Protection

The **high-sensitivity PIR (passive infrared) motion detector** has an adjustable design allowing the detection angle to be set, with a **180º** range. It offers 3 sensitivity settings to suit different environments and needs. It runs on 230V and supports a maximum load of **300W LED**.

With an adjustable detection range of **5 to 12 metres**, an adjustable time delay from 10 seconds to 7 minutes and ambient light detection from 3 to 2000 lux, it offers precise switch-on control. Easy to install, it includes the accessories needed for wall mounting and, thanks to its **IP44** rating, can be installed indoors or in protected outdoor areas.

Why choose this product? **? PIR 180º, 3 settings**
Adjustable sensitivity, range and delay. **? 230V, max 300W LED**
5-12 m detection, 3-2000 lux threshold. **? IP44, black**
Indoor and protected outdoor, wall mounting. Technical specifications Product typePIR wall motion detectorDetection angle180º (adjustable)Settings3 (sensitivity, delay, light)Voltage230VMax. load300W LEDRange5-12 m (adjustable)Time delay10 s to 7 minLight threshold3-2000 luxColourBlackProtectionIP44 Advantages

- **PIR 180º:** high sensitivity.
- **3 settings:** range, delay, lux.
- **230V, 300W LED:** max load.
- **5-12 m:** adjustable detection.
- **10 s-7 min:** time delay.
- **Black IP44:** in./protected out.

Recommended applications ?**Entrances and corridors** — automatic switch-on.?**Garages and stairs** — security.?**Facades and porches** — IP44.?**Energy savings** — detection lighting. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Fix to the wall**
Mount the detector with the included accessories.3**Wire it**
Wire to 230V and the load (max 300W LED).4**Adjust**
Set sensitivity, delay and light threshold. Frequently asked questions **What is its range?**
Between 5 and 12 metres, adjustable, over 180º. **What load does it support?**
Up to 300W LED, at 230V. **Can the time delay be set?**
Yes, from 10 seconds to 7 minutes. ?

PIR 180º
IP44?

230V
300W?

10s-7min
5-12m?

In stock
Fast shipping

Product gallery:











