6W Recessed Square LED Downlight 6W 117x117mm Silver Grey IP20

Product codes:

Reference: PL-DCP6W



Product features:

Power (W): 6
Power source (V): 100-240V
Color temperature CCT: 4000K
LED: SMD2835
Brightness (Lm): 600
Color rendering index (Ra):: ?80
Colour: Plata
IP: IP20
Luminous angle: 120º
Frequency (Hz): 50-60Hz
Forma: Cuadrado
Measures (mm): 117x117x11mm
Medida de corte (mm.): 100x100mm
Material: Aluminum + PC
Operating temperature: -20ºC ~ +40ºC
Energy efficiency 2021: A+
Energy efficiency 2023: G
Lifespan: 25.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Natural white 4000K

Product description:

6W square slim downlight, silver grey, 600 lm, IP20 Square Slim Recessed LED Downlight 6W Silver Grey 117x117 mm 600 lm IP20

The in silver grey offers with an design (11 mm thick). Ideal for shallow false ceilings, elegant, contemporary finish, dimensions 117x117 mm (100 mm cut-out), IP20 rating.

? 6W? 600 lm? 117x117? IP20

6W
Power600 lm
Luminous flux117x117 mm
DimensionsIP20
Protection

The **6W silver-grey square slim recessed LED downlight** is the ideal solution for those seeking a modern, discreet, high-performance recessed ceiling LED spot. Thanks to its **ultra-thin** design (11 mm), it fits easily into shallow false ceilings, while bringing an elegant, contemporary finish.

Made with a silver-grey frame and an efficient LED chip, it provides a flux of **600 lumens** for clear, even lighting. Dimensions 117x117 mm, 100 mm cut-out, **IP20** rating. Ideal for living rooms, corridors, bedrooms, offices and shops needing discreet, neat recessed lighting.

Why choose this product? **? Ultra-thin 11 mm design**

Fits into shallow false ceilings. **? Square 117x117 mm**

Elegant silver grey, 100 mm cut-out, IP20. **? 6W, 600 lm**
Clear, even, discreet lighting. Technical specifications Product typeSquare slim recessed LED downlightPower6WLuminous flux600 lmDimensions117x117 mmThickness11 mmCut-out100 mmColourSilver greyProtectionIP20UseIndoor Advantages

- **Slim 11 mm:** shallow false ceilings.
- **Square 117x117 mm:** silver grey.
- **6W, 600 lm:** even.
- **100 mm cut-out:** recessed.
- **IP20:** indoor.
- **Discreet:** contemporary finish.

Recommended applications ?**Living rooms and bedrooms** — discreet lighting.?**Corridors and offices** — slim 11 mm.?**Shops** — contemporary finish.?**False ceilings** — shallow. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Make the cut-out**
Prepare a 100 mm cut-out in the ceiling.3**Recess and wire**
Insert the downlight and wire the driver.4**Check**

Restore power and check the lighting. Frequently asked questions **What is its thickness?**

Only 11 mm, ultra-thin design. **What cut-out does it need?**

A 100 mm cut-out (117x117 mm outer). **What is its colour?**
Silver grey, contemporary finish. ?

6W
600 lm?

117x117
11 mm?

IP20
Silver?

In stock
Fast shipping

Product gallery:



