40W Black Monophasic LED Track Spotlight CCT Bridgelux chip CRI90 38º-60º 4550Lm

Product codes:

Reference: PL-FCMN40-CCT



Product features:

Power (W): 40
Power source (V): 220-240V
Color temperature CCT: Seleccionable 3000K-4000K-6000K
LED: COB
LED chip brand: BRIDGELUX
Brightness (Lm): 4550
Color rendering index (Ra):: ?90
Colour: Black
IP: IP20
IK: IK05
Luminous angle: 38º / 60º
Frequency (Hz): 50-60Hz
Power factor ?: 0.90
Measures (mm): Ø80x180x160mm
Material: Aluminum + PC
Driver: KGP no flicker
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2021: A+
Energy efficiency 2023: E
Lifespan: 30.000h
Certification: CE - RoHS
Warranty: 5 años

Product attributes:

Product description:

Single-phase track floodlight black 40W, CCT, BRIDGELUX Track LED Floodlight single-phase black 40W CCT BRIDGELUX Chip 4550 lm Interchangeable Optics

The with a chip offers a selector (3000K / 4000K / 6000K) and up to . Interchangeable optics, modern design, ideal for professional lighting of shops and exhibitions.

? 40W? CCT? BRIDGELUX? 4550 lm

40W
PowerCCT
TemperaturesBRIDGELUX
LED chipSingle-phase
Track

The **single-phase track LED floodlight**, in black, is the ideal solution for professional lighting of shops, boutiques and exhibition spaces. With a **BRIDGELUX** chip and a **CCT** selector (3000K, 4000K, 6000K), it delivers up to **4550 lumens** and lets you adapt the lighting atmosphere to every need.

Its **interchangeable optics** let you adjust the beam (angle) according to the desired highlighting, from products to displays. Its modern black design fits into any environment. Easy click mounting on the single-phase track, for modular, precise, efficient lighting.

Why choose this product? **? CCT selector**

3000K, 4000K or 6000K to suit the space. **? BRIDGELUX chip**

4550 lm, interchangeable optics. **? Single-phase track**
Click mounting, modern black design. Available light shades

Available in three selectable colour temperatures, to match the atmosphere of each space:

3000 K
Warm white4000 K
Neutral white6000 K
Cool white Technical specifications Product typeSingle-phase track LED floodlightPower40WLuminous fluxUp to 4550 lmColour temperatureCCT 3000K / 4000K / 6000KLED chipBRIDGELUXOpticsInterchangeableColourblackUseShops, exhibitions Advantages

- **Single-phase track:** black.
- **CCT selector:** 3000/4000/6000K.
- **BRIDGELUX:** up to 4550 lm.
- **Interchangeable optics:** adjustable beam.
- **40W:** professional lighting.
- **Click mounting:** modular.

Recommended applications ?**Shops and boutiques** — professional lighting.?**Showrooms and exhibitions** — highlighting.?**Galleries** — CCT of choice.?**Museums** — interchangeable optics. Installation guide 1**Switch off the power**
Cut the track supply.2**Choose the temperature**
Set the CCT selector (3000/4000/6000K).3**Mount the floodlight**
Click the floodlight onto the single-phase track.4**Aim and check**
Aim the beam and check the lighting. Frequently asked questions **Can the temperature be chosen?**

Yes, CCT selector 3000K, 4000K or 6000K. **Are the optics interchangeable?**

Yes, to adjust the beam as needed. **Which track does it mount on?**
On a single-phase track. ?

40W
4550 lm?

CCT
BRIDGELUX?

Single-phase
Black?

In stock
Fast shipping

Product gallery:








WW NW CW

