15W Recessed LED Downlight Adjustable Diameter Ø40-170mm

Product codes:

Reference: DLRBDAJ15



Product features:

Power (W): 15
Power source (V): 100-240V
Color temperature CCT: 3000K
Color temperature CCT: 4000K
Color temperature CCT: 6500K
LED: SMD2835
LED chip brand: SAN'AN
Dimmable: Sí, TRIAC
Dimmable: DALI
Dimmable: 1/10V
Brightness (Lm): 1520
Color rendering index (Ra):: ?80
Colour: White
IP: IP20
IK: IK06
Luminous angle: 0.90
Frequency (Hz): 50-60Hz
Power factor ?: 0.90
Forma: Redondo
Measures (mm): Incluido, sin flicker
Medida de corte (mm.): Ø40mm ~ Ø170mm
Material: Aluminum + glass
Driver: Incluido, sin flicker
Operating temperature: -20ºC ~ +40ºC
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 35.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Warm white 3000K, Natural white 4000K, Cool white 6500K
Dimming system: No dimming (On/Off), TRIAC, 1-10V, DALI

Product description:

15W downlight, adjustable Ø40-170 mm, 1520 lm Recessed Round LED Downlight 15W 1520 lm Adjustable Diameter Ø40-170 mm

The offers with an that fits different cut-outs. SANAN SMD2835 chip, aluminium and opal PC, even shadow-free lighting, IP40 rating, ideal for renovation.

? 15W? 1520 lm? Ø40-170 mm? Réglable

15W
Power1520 lm
Luminous fluxØ40-170 mm
Adjustable cut-outIP40
Protection

The **15W round recessed LED downlight**, with a luminous flux of **1520 lumens**, stands out for its **adjustable base** that fits different cut-out diameters, from **40 mm to 170 mm**. It is the ideal solution for renovation and replacement of spots with varying cut-out dimensions.

It has a high-performance **SANAN SMD2835** LED chip and is made of aluminium and opal PC, offering intense, even lighting, **without shadows or dark areas**. With a Ø175 mm external diameter and an IP40 rating, it installs easily in the false ceilings of living rooms, corridors, offices and shops.

Why choose this product? **? Adjustable Ø40-170 mm diameter**
Fits any cut-out, ideal for renovation. **? SANAN SMD2835, 1520 lm**
Intense, even lighting, shadow-free. **? Aluminium and opal PC**
Ø175 mm outer, IP40, easy installation. Technical specifications Product typeAdjustable-diameter recessed LED downlightPower15WLuminous flux1520 lmAdjustable cut-outØ40-170 mmOuter diameterØ175 mmLED chipSANAN SMD2835MaterialAluminium and opal PCProtectionIP40UseIndoor / renovation Advantages

- **Ø40-170 mm:** adjustable diameter.
- **15W, 1520 lm:** SANAN SMD2835.
- **Shadow-free:** opal PC.
- **Ø175 mm:** outer.
- **IP40:** indoor.
- **Renovation:** any cut-out.

Recommended applications ?**Renovations** — varying cut-out.?**Living rooms and corridors** — shadow-free.?**Offices and shops** — 1520 lm.?**False ceilings** — Ø40-170 mm. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Set the diameter**
Adjust the base to the cut-out (Ø40-170 mm).3**Recess and wire**
Insert the downlight and wire the driver.4**Check**
Restore power and check the lighting. Frequently asked questions **Which cut-out diameters does it accept?**
From Ø40 mm to Ø170 mm, adjustable base. **What is its luminous flux?**
1520 lumens for 15W. **Is it suitable for renovation?**
Yes, its adjustable base fits existing cut-outs. ?

15W
1520 lm?

Ø40-170
Adjustable?

SANAN
IP40?

In stock
Fast shipping

Product gallery:


Movable-Movible-Beweglich-Mobile-Móvel-




170mm
40mm