SGL Selectable CCT 3000K+4000K 20W 2300Lm Solar LED Street Light

Product codes:

Reference: SGL200



Product features:

Power (W): 20
Color temperature CCT: Selectable 3000K-4000K
LED: SMD2835
Luminous efficacy (Lm/W): 115
Brightness (Lm): 2300
Color rendering index (Ra):: ?80
Colour: Black
IP: IP65
IK: IK06
Luminous angle: 360º
Measures (mm): Ø400x120mm
Material: ABS
Operating temperature: -20ºC ~ +40ºC
Lifespan: 25.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K)

Product description:

SGL 20W solar street light, CCT, 360º, autonomous SGL Solar LED Street Light 20W 2300 lm CCT 3000K/4000K IP65 360º Diffuser

The provides
for outdoor spaces. Black body, 360º
opal diffuser, 11.5W monocrystalline panel, selector,
IP65 rating, off the mains.

? Solaire? 2300 lm? CCT? IP65

20W
Power2300 lm
Luminous flux3000K/4000K
CCTIP65
Protection

The **20W SGL solar LED street light** is designed to provide efficient, autonomous lighting for outdoor spaces. Made of **flame-retardant anti-UV ABS+PC** with a black body and a **360º opal diffuser**, it is ideal for paths, parks, gardens and residential areas, with a luminous flux of **2300 lumens**.

It has an **11.5W monocrystalline solar panel** and a rechargeable battery, for operation **off the mains**: it recharges during the day and switches on automatically at night. Its **CCT (3000K or 4000K)** selector lets you adapt the atmosphere, and its **IP65** rating makes it resistant to rain and dust. Dimensions Ø400x120 mm, mounting on a Ø60-65 mm tube.

Why choose this product? **? 100% solar**

11.5W monocrystalline panel, off the mains. **? CCT 3000K/4000K, 360º**

Opal diffuser, adaptable atmosphere, 2300 lm. **? IP65, anti-UV ABS+PC**

Flame-retardant, rain- and dust-resistant, auto switch-on. Technical specifications Product typeSGL solar LED street lightPower20WLuminous flux2300 lmColour temperatureCCT 3000K / 4000KDiffuser360º opalSolar panelMonocrystalline 11.5WMaterialFlame-retardant anti-UV ABS+PC (black)ProtectionIP65DimensionsØ400x120 mmMountingØ60-65 mm tubeUseOutdoor Advantages

- **100% solar:** 11.5W panel.
- **CCT 3000K/4000K:** of choice.
- **2300 lm, 360º:** opal diffuser.
- **IP65:** anti-UV ABS+PC flame-retardant.
- **Automatic switch-on:** at night.
- **Ø400x120 mm:** Ø60-65 mm tube.

Recommended applications ?**Paths and parks** — solar lighting.?**Gardens and residential areas** — off the mains.?**Private drives** — 360º diffuser.?**Remote areas** — solar autonomy. Installation guide 1**Install the panel**
Expose the solar panel to daylight.2**Mount on the tube**
Fix the street light on a Ø60-65 mm tube.3**Choose the temperature**
Select CCT 3000K or 4000K.4**Activate**

Switch on; automatic switch-on at night. Frequently asked questions **Is an electrical installation needed?**

No, it works on solar energy, off the mains. **Can the temperature be chosen?**

Yes, CCT 3000K or 4000K. **What is its luminous flux?**

2300 lumens, 360º opal diffuser. ?

Solar

2300 lm?

CCT

360º?

IP65

20W?


In stock

Fast shipping

Product gallery:






Ø400 mm
120 mm







