38W CCT Tilting Rectangular LED Downlight OSRAM/PHILIPS 5980Lm

Product codes:

Reference: IL-4412OSR



Product features:

Power (W): 38
Power source (V): 220-240V
Color temperature CCT: Seleccionable 3000K-4000K-6000K
LED: SMD2835
LED chip brand: OSRAM
Luminous efficacy (Lm/W): 160
Brightness (Lm): 5980
Color rendering index (Ra):: ?80
Colour: White
IP: IP20
Luminous angle: 60º
Frequency (Hz): 50-60Hz
Power factor ?: 0.95
Measures (mm): 240x145x85mm
Material: Aluminum + PC
Driver: Philips Flicker-free
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2021: A+
Energy efficiency 2023: D
Lifespan: 30.000h
Certification: CE - RoHS
Warranty: 5 años

Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K-6000K)

Product description:

38W rectangular orientable downlight, CCT, OSRAM/PHILIPS Rectangular Orientable LED Downlight 38W 5980 lm CCT OSRAM PHILIPS Driver

The with an chip and driver offers with a selector (3000K / 4000K / 6000K). 60º orientable beam, dimensions 240x145x85 mm (210x130 mm cut-out), IP20.

? 38W? 5980 lm? CCT? Orientable

38W
Power5980 lm
Luminous fluxCCT
Temperatures60º
Orientable

The **38W rectangular orientable LED downlight** combines the quality of an **OSRAM** chip and a **PHILIPS** driver for powerful, reliable lighting of **5980 lumens**. Its **adjustable CCT system** (3000K, 4000K, 6000K) lets you create varied atmospheres, from warm to cool, in any residential or commercial space.

Its **orientable (60º)** beam precisely directs the light to highlight products, artworks or work areas. Recessed (dimensions 240x145x85 mm, 210x130 mm cut-out) and with an IP20 rating, it is the ideal solution for shops, showrooms, halls, offices and hotels requiring professional accent lighting.

Why choose this product? **? CCT selector**
3000K, 4000K or 6000K, varied atmospheres. **? OSRAM + PHILIPS driver**
5980 lm, powerful and reliable. **? Orientable 60º**
Highlights products and areas, recessed. Available light shades

Available in three selectable colour temperatures, to match the atmosphere of each space:

3000 K
Warm white4000 K
Neutral white6000 K
Cool white Technical specifications Product typeRectangular orientable LED downlightPower38WLuminous flux5980 lmColour temperatureCCT 3000K / 4000K / 6000KLED chipOSRAMDriverPHILIPSBeam60º (orientable)Dimensions240x145x85 mm (210x130 mm cut-out)ProtectionIP20 Advantages

- **CCT:** 3000/4000/6000K.
- **OSRAM + PHILIPS:** 5980 lm.
- **Orientable 60º:** directable beam.
- **Rectangular:** 210x130 mm cut-out.
- **IP20:** indoor.
- **Shops and showrooms:** accent lighting.

Recommended applications ?**Shops and showrooms** — accent lighting.?**Halls and hotels** — 5980 lm orientable.?**Offices** — CCT of choice.?**Museums and galleries** — OSRAM/PHILIPS. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Choose the temperature**
Set the CCT selector (3000/4000/6000K).3**Recess**
Make a 210x130 mm cut-out and insert the spot.4**Aim and wire**
Aim the beam, wire the PHILIPS driver. Frequently asked questions **Can the temperature be chosen?**
Yes, CCT selector 3000K, 4000K or 6000K. **Is it orientable?**
Yes, 60º orientable beam. **Which driver does it use?**
A PHILIPS driver, with OSRAM chip, 5980 lm. ?
38W
5980 lm?
CCT
OSRAM?
60º
PHILIPS?
In stock
Fast shipping

Product gallery:








WW-NW-CW

