

7W Selectable CCT Black Recessed Adjustable LED Downlight 700Lm URG17

Product codes:

Reference: LSPL7W-CCT-91270



Product features:

Power (W): 7
Power source (V): 220-240V
Color temperature CCT: Seleccionable
3000K-4000K-6000K
LED: COB
Luminous efficacy (Lm/W): 100
Brightness (Lm): 700
CRI: +80
Colour: Black
IP: IP40
IK: IK06
Luminous angle: 60°
Frequency (Hz): 50-60Hz
Power factor: 0.50
Measures (mm): Ø90x45mm
Medida de corte (mm.): Ø70mm
Material: Thermoplastic
Operating temperature: -20°C ~ +40°C
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 25.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (°K): Selectable CCT (3000K-4000K-6000K)

Product description:

7W Black Recessed Circular Adjustable LED Downlight UGR17 This **7W recessed circular LED downlight** offers a modern and minimalist design in black, perfect for high-quality indoor lighting. With its ability to tilt up to 24° and a 60° light optic, this spotlight is ideal for precise and efficient illumination.

Equipped with a CCT temperature selector that allows switching between warm, neutral, and cool light, it adapts to different environments and preferences. Its black color design and PC construction make it durable and aesthetically pleasing, suitable for various spaces such as homes, offices, and shops. It includes a removable honeycomb grid that allows optimal light control with a UGR17 rating, minimizing glare.

Technical Specifications

- **Power:** 7W
- **LED Chip:** COB
- **Luminous Flux:** 700 lumens
- **Light Optic:** 60°

- **Adjustable:** Up to 24°
- **CCT Selector:** Warm, neutral, and cool
- **Material:** PC
- **Color:** Black
- **IP Rating:** IP40
- **Dimensions:** Ø90x45mm
- **Cut-out Dimensions:** Ø70mm
- **Honeycomb Grid:** Removable, UGR17
- **Driver and Connections:** Integrated into the spotlight

Installation Instructions

Installing this LED downlight is simple thanks to its integrated driver and connections system:

1. Mark and cut an opening in the ceiling with a diameter of Ø70mm.
2. Connect the integrated driver to the power supply, ensuring the power is turned off.
3. Insert the downlight into the opening, adjusting its orientation to achieve the desired angle.
4. Turn on the power and select the desired color temperature using the CCT selector.

Recommended Applications

Thanks to its versatile design and energy efficiency, this LED downlight is perfect for a wide range of applications such as:

- Decorative and functional lighting in homes.
- Reception areas and corridors in offices.
- Showcases and exhibition areas in shops.
- Focused lighting in museums and galleries.

Product gallery:



