

## 60x60cm 40W LED Panel LIFUD Driver 4000Lm

### Product codes:

Reference: IL-PL40WEC



### Product features:

Power (W): 40  
Power source (V): 220-240V  
Color temperature CCT: 4000K  
Color temperature CCT: 6000K  
LED: SMD2835  
Luminous efficacy (Lm/W): 100  
Brightness (Lm): 4000  
CRI: +82  
Colour: White  
IP: IP20  
Luminous angle: 120°  
Frequency (Hz): 50-60Hz  
Power factor: 0.9  
Measures (mm): 595x595x35mm  
Material: Aluminum + PC  
Driver: LIFUD Flicker Free  
Operating temperature: -20°C ~ +55°C  
Energy efficiency 2021: A+  
Energy efficiency 2023: E  
Lifespan: 35.000h  
Certification: CE - RoHS  
Warranty: 3 años

### Product attributes:

Color temperature CCT (°K): Natural white 4000K, Cool white 6000K

### Product description:

60x60cm LED panel, with a power of 40W and a luminous flux of 4000 lumens, offering excellent performance and a perfect quality/price ratio, with a 3-year warranty.

LIFUD Flicker-free driver, without flickering.

The panel is constructed using a backlight system, in such a way that the light is emitted uniformly without dark zones and transmitting less heat, thereby increasing the panel's lifespan.

Dimensions: 595x595x35mm

### Product gallery:

