# 12W 1200Lm cut-out Ø150mm Selectable CCT LED panel

## Product codes:

Reference: DLE12W



## Product features:

Power (W): 12
Power source (V): 220-240V
Color temperature CCT: Seleccionable 3000K-4000K-6000K
LED: SMD2835
Brightness (Lm): 1200
Color rendering index (Ra):: ?80
Colour: White
IP: IP20
Luminous angle: 120º
Frequency (Hz): 50-60Hz
Forma: Redondo
Measures (mm): Ø168x11mm
Medida de corte (mm.): Ø150mm
Material: Aluminum + PC
Operating temperature: -20ºC ~ +40ºC
Energy efficiency 2021: A+
Energy efficiency 2023: G
Lifespan: 25.000h
Certification: CE - RoHS
Warranty: 3 años

## Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K-6000K)

## Product description:

12W LED Downlight Panel 1200Lm Selectable CCT 3000K/4000K/6000K

12W Circular Recessed LED Downlight Panel with a luminous flux of 1200 lumens , and an outer diameter of 168mm . Made of high-quality aluminum, lacquered in white with an excellent finish, and opal PC diffuser for anti-glare.

The 12W LED downlight is perfect for installation in 150/160mm diameter holes , and its outer frame covers irregularities up to 168mm in diameter.

Thanks to its ultra-thin slim design of just 1cm thickness, it can be installed in plasterboard and aluminum ceilings,

especially in those ceilings with limited space behind. Remember that the downlight panel comes with an external LED driver , which should be placed above the false ceiling.

Technical specifications Selectable CCT 3000K/4000K/6000KOuter diameterØ168mmCeiling cutoutØ150/160mmFor indoor use (IP20).Driver included. House Recommendation:

Whenever possible, try to place the driver above the ceiling and not on the panel. This way, you wonot t transfer the heat from the downlight to the driver, increasing the lifespan of the equipment.

Usage Recommendations for the 12W LED Downlight

- Homes
- Commercial spaces
- Schools and libraries
- Offices
- Hotels and restaurants
- Government buildings

?

## Certified product

CE?

## In stock

Fast shipping

### Product gallery:






