Empty Tri-Proof Light 60cm IP65 for 2 LED Tube

Product codes:

Reference: PL-1126



Product features:

Lampholder: G13
IP: IP65
IK: IK08
Measures (mm): 670x95x60mm
Material: ABS
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Product description:

IP65 waterproof batten for LED tubes Empty IP65 Waterproof Fitting for Two 60 cm LED Tubes

An waterproof fitting ready to take two LED tubes. In ABS and polycarbonate, with a translucent diffuser and single-end connection, it protects your tubes in damp or dusty environments.

? IP65? 2x 60 cm? G13? ABS + PC

IP65
Protection60 cm
Tube2
No. of tubesG13

Connection

The **IP65 waterproof fitting** is an empty batten prepared for installing **two 60 cm LED tubes**. With an **IP65** protection rating, it effectively protects the tubes against dust and water jets, making it ideal for demanding environments.

Made from **ABS and polycarbonate**, with a grey base and a **translucent diffuser** that lets light through without loss of intensity, it has a compact **670 x 95 x 60 mm** design. It is supplied pre-wired, with G13 lampholders and single-end connection, and accepts any of our 60 cm LED tubes.

Why choose this product? **? IP65 protection**
Resists dust and water jets. **? Pre-wired G13**
Quick installation with single-end connection. **? ABS and polycarbonate**
Sturdy and durable, with a translucent diffuser and no light loss. Technical specifications Product typeWaterproof fitting for LED tubesProtectionIP65Number of tubes2Compatible tube length60 cmConnectionG13 lampholders, single-endMaterialABS and polycarbonateDiffuserTranslucentDimensions670 x 95 x 60 mmWiringPre-wired Advantages

- **IP65 sealing:** suited to damp and dusty environments.
- **For 2x 60 cm tubes:** compatible with all our LED tubes.
- **Pre-wired G13:** quick single-end installation.
- **ABS and polycarbonate:** sturdy and durable.
- **Translucent diffuser:** light with no loss of intensity.

Recommended applications ?**Garages and workshops** — waterproof technical lighting.?**Warehouses and storage areas** — dusty environments.?**Car parks** — rugged lighting.?**Industrial kitchens and damp rooms** — IP65 protection.
Installation guide 1**Switch off the power**
Cut the supply before installation.2**Fix the fitting**
Fix the fitting to the ceiling or wall using the included brackets.3**Install the tubes**
Insert the 60 cm LED tubes and seat them on the G13 lampholders.4**Connect and close**
Make the single-end connection, close the fitting and restore power. Frequently asked questions **Which tubes can I use?**
Any of our 60 cm LED tubes with single-end connection. **What is its protection rating?**
IP65: resistant to dust and water jets. **Is it supplied wired?**
Yes, it is pre-wired with G13 lampholders and single-end connection. ?

IP65
Waterproof?

G13
Pre-wired?

ABS + PC
Sturdy?

In stock
Fast shipping

Product gallery:





