7W CCT BARI ICE WHITE Recessed LED Spot

Product codes:

Reference: BARI7W



Product features:

Power (W): 7
Power source (V): 220-240V
Color temperature CCT: Seleccionable 3000K-4000K-6000K
LED: COB
LED chip brand: BRIDGELUX
Luminous efficacy (Lm/W): 140
Brightness (Lm): 964
Color rendering index (Ra):: ?95
Colour: White
IP: IP20
Luminous angle: 36º
Frequency (Hz): 50-60Hz
Measures (mm): Ø65x62mm
Medida de corte (mm.): Ø55mm
Material: Aluminum
Driver: LIFUD Flicker Free
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2021: A+
Energy efficiency 2023: C
Lifespan: 35.000h
Certification: CE - RoHS
Warranty: 5 años

Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K-6000K)

Product description:

Recessed spot, selectable CCT, CRI > 95 Recessed LED Spot 7W CCT 36º UGR17 - matte white

The with a BridgeLUX COB chip and LIFUD driver offers 964 lumens, a 36º beam, and UGR 17. Selectable CCT temperature (3000K/4000K/6000K), Ø65x62 mm, Ø55 mm cut-out, matte white finish.

? 7W? 964 lm? CRI > 95? UGR 17

7W

Power 964 lm
Luminous flux 36º
Beam CRI > 95
Colour rendering

The **7W mini recessed LED spot** is the perfect solution for those seeking versatile, high-quality lighting. With a CCT colour-temperature selector built into the cable, you can choose between 3000K, 4000K and 6000K to suit your needs. Its compact Ø65x62 mm dimensions and Ø55 mm ceiling cut-out allow easy, discreet installation.

Made of aluminium with a matte white finish, this spot offers an elegant, modern design. Fitted with a **BridgeLUX COB 2630 DS-C30** LED chip, it provides 964 lumens with a 36º beam, ideal for focused lighting. Its **CRI > 95** ensures faithful colour rendering and its UGR 17 great visual comfort. The LIFUD driver guarantees high durability and flicker-free lighting.

Why choose this product? **? Selectable CCT**

3000K, 4000K or 6000K via the selector on the cable. **? CRI > 95, UGR 17**

Faithful colour rendering and great visual comfort. **? LIFUD driver**
Flicker-free, high durability. Available light shades

Available in three selectable colour temperatures, to match the atmosphere of each space:

3000 K
Warm white 4000 K
Neutral white 6000 K
Cool white Technical specifications Product type Recessed LED spot Power 7W Luminous flux 964 lm LED chip BridgeLUX COB 2630 DS-C30 Colour temperature Selectable CCT (3000K/4000K/6000K) Beam 36º CRI > 95 UGR 17 Dimensions Ø65x62 mm Ceiling cut-out Ø55 mm Material Aluminium Finish matte white Driver Flicker-free LIFUD Advantages

- **Selectable CCT:** 3000K, 4000K or 6000K.
- **CRI > 95:** faithful colour rendering.
- **UGR 17:** low glare.
- **LIFUD driver:** flicker-free.
- **Compact Ø65x62 mm:** discreet Ø55 mm cut-out.
- **36º beam:** focused lighting.

Recommended applications ? **Living rooms and bedrooms** — accent lighting. ? **Shops and hotels** — faithful colour rendering. ? **Corridors and false ceilings** — discreet integration. ? **Showrooms** — product highlighting. Installation guide 1 **Prepare the cut-out**
Make a Ø55 mm cut-out in the ceiling. 2 **Choose the temperature**
Set the CCT selector (3000K, 4000K or 6000K). 3 **Wire it**
Connect the LIFUD driver to the mains. 4 **Recess it**

Insert the spot into the cut-out and check the lighting. Frequently asked questions **How to choose the temperature?**

Via the CCT selector on the cable: 3000K, 4000K or 6000K. **What ceiling cut-out?**

Ø55 mm (spot dimensions Ø65x62 mm). **What is the colour rendering?**
CRI > 95, with UGR 17 for low glare. ?

7W
964 lm ?

CRI > 95
UGR 17 ?

CCT
3000K-4000K-6000K ?

LIFUD
Flicker-free

Product gallery:








62
Ø65

