# 45W 150cm Waterproof LED Batten Radar Sensor - allways on 20% 4950Lm IP65

## Product codes:

Reference: ESR45W



## Product features:

Power (W): 45
Power source (V): 100-240V
Color temperature CCT: 4000K
Color temperature CCT: 6500K
Brightness (Lm): 4950
IK: IK08
Luminous angle: 120º
Measures (mm): 1500x80x36mm
Material: PC
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2021: A+
Lifespan: 30.000h
Certification: CE - RoHS
Warranty: 3 años

## Product attributes:

Color temperature CCT (ºK): Natural white 4000K, Cool white 6500K

## Product description:

Slim batten with radar detector, IP65 / IK08 Waterproof LED Batten 45W 150 cm Radar Sensor + 20% Permanent Light 4950 lm IP65

The (150 cm) with an ultra-thin silver aluminium design delivers . Radar presence detector: 20% permanent light that rises to 100% on detection. IP65 and IK08, indoor and outdoor.

? 45W? 4950 lm? Radar? IP65

45W
Power4950 lm
Luminous fluxRadar
SensorIP65 / IK08
Protection

The **slim waterproof LED batten 45W** is a modern, efficient lighting solution, with an ultra-thin design in elegant silver aluminium and an opal PC diffuser. With a length of 150 cm, it offers a luminous flux of 4950 lumens thanks to its integrated high-brightness SMD2835 LED, ideal for a wide range of applications.

It is wired at one end and features an advanced **radar presence detector**: the luminaire stays on at 20% permanently and rises to 100% when presence is detected, optimising consumption and improving safety. Its **IP65** rating and **IK08** impact resistance make it suitable for indoor and outdoor use, protecting it against dust, water jets and impacts.

Why choose this product? **? Radar detector**

20% permanently, 100% on presence detection. **? IP65 / IK08**

Waterproof and impact-resistant, in/out. **? Slim design**
Silver aluminium and opal diffuser, 4950 lm. Technical specifications Product typeSlim waterproof LED batten with radar sensorPower45WLength150 cmLuminous flux4950 lmLEDIntegrated high-brightness SMD2835SensorRadar presence detectorModePermanent 20% ? 100% on detectionMaterialSilver aluminium + opal PC diffuserProtectionIP65Impact resistanceIK08InstallationWired at one endDimensions1500x80x36 mm Advantages

- **Radar detector:** 20% permanent, 100% on detection.
- **IP65 / IK08:** waterproof and impact-resistant.
- **Slim design:** silver aluminium, opal diffuser.
- **SMD2835:** high brightness and efficiency.
- **Energy savings:** adaptive lighting.
- **Indoor/outdoor:** versatile installation.

Recommended applications ?**Garages and car parks** — detection-based lighting.?**Corridors and stairs** — safety and savings.?**Cellars and passageways** — adaptive light.?**Warehouses** — waterproof IP65 lighting. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Fix the batten**
Fix the batten to the ceiling or wall.3**Wire at one end**
Make the wired connection at one end.4**Check the sensor**

Restore power and test detection (20% ? 100%). Frequently asked questions **How does the sensor work?**

It keeps 20% light permanently and rises to 100% on detection. **Is it suitable for outdoors?**

Yes, IP65 and IK08 suit indoor and outdoor use. **What is the luminous flux?**
4950 lumens, with a high-brightness SMD2835 LED. ?


## 45W
4950 lm?

## Radar
20%?100%?

## IP65
IK08?

## In stock
Fast shipping

### Product gallery:


20%
8m
100%
8m
100%
+30 secs.
8m
20%
8m








45W
150CM