60cm Tri-Proof fixture for LED Tube multi-connection IP65

Product codes:

Reference: PETP118

Product features:

Lampholder: G13
IP: IP65
IK: IK08
Measures (mm): 660x85x95mm
Material: ABS
Operating temperature: -20ºC ~ +40ºC
Certification: CE - RoHS
Warranty: 2 años



Product attributes:

Product description:

High-pressure washable ABS housing for T8 tubes Empty Waterproof Housing for 1 LED T8 tube 60 cm IP65

The is a practical, sturdy solution to install (not included). In ABS with a transparent polycarbonate cover, IP65, high-pressure washable. 1-end connection (starter fuse in the holder) or 2-end (no starter).

? 60 cm? IP65? ABS+PC? Lavable

60 cm
For 1 T8 tube(s)IP65

ProtectionABS+PC
MaterialWashable
High pressure

The **empty waterproof housing** is a practical, sturdy solution for installing 1 LED T8 tube 60 cm (not included). Made of **ABS plastic with a transparent polycarbonate cover**, it guarantees durability and protection in various conditions.

With **IP65** protection, it suits indoor and outdoor installations, offering high resistance to humidity and dust. It can be washed at high pressure, easing maintenance. 1-end connection (starter fuse in the holder) or 2-end (no starter). Dimensions: 660x85x95 mm.

Why choose this product? **? IP65 waterproof**

Resists humidity and dust, high-pressure washable. **? ABS + PC cover**

Durable and sturdy, indoor and outdoor. **? For 1 T8 tube(s)**

Compatible with 1 LED T8 tube 60 cm (not included). Technical specifications Product typeEmpty waterproof housing for T8 LED tubeFor1 LED T8 tube 60 cm (not included)MaterialABS + transparent polycarbonate coverProtectionIP65 (indoor/outdoor)MaintenanceHigh-pressure washableConnection1-end connection (starter fuse in the holder) or 2-end (no starter).Dimensions660x85x95 mmLED tubeNot included Advantages

- **IP65 waterproof:** humidity and dust.
- **High-pressure washable:** easy maintenance.
- **ABS + PC cover:** durable and sturdy.
- **For 1 T8 tube(s):** 60 cm (not included).
- **Indoor/outdoor:** versatile installation.

Recommended applications ?**Garages and basements** — waterproof lighting.?**Industrial and commercial areas** — humidity resistance.?**Warehouses and workshops** — IP65 robustness.?**Car parks and outdoors** — dust/water exposure. Installation guide 1**Prepare the tube**
Get 1 LED T8 tube 60 cm (not included).2**Install the tube(s)**
Place the T8 tube(s) in the housing.3**Fix the housing**
Fix the housing to the ceiling or wall.4**Close and check**

Close the PC cover and check the sealing. Frequently asked questions **Is the LED tube included?**

No, the housing is empty (tube not included). **How does it connect?**

1-end connection (starter fuse in the holder) or 2-end (no starter). **Is it suitable for outdoors?**
Yes, IP65 and high-pressure washable, indoor and outdoor. ?

IP65
60 cm?

ABS+PC
Washable?

1 tube(s)
T8?

In stock
Fast shipping

Product gallery:





1xT8
60cm