10W 60cm IP20 LED Batten 960Lm

Product codes:

Reference: PL-P10W-6



Product features:

Power (W): 10
Power source (V): 100-240V
Color temperature CCT: 2700K
Color temperature CCT: 4000K
Color temperature CCT: 6500K
LED: SMD2835
Brightness (Lm): 960
Color rendering index (Ra):: ?80
Colour: Plata
IP: IP20
IK: IK08
Luminous angle: 180º
Frequency (Hz): 50-60Hz
Measures (mm): 600x75x25mm
Material: Aluminum + PC
Operating temperature: -20ºC ~ +40ºC
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 35.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Warm white 2700K, Cool white 6500K

Product description:

Slim linear batten, aluminium + PC, IP20 / IK08 Linear LED Batten 10W 60 cm 960 lm IP20

The (60 cm) in aluminium and polycarbonate delivers with a 180º angle. High-brightness SMD2835 chip, IP20, IK08, for efficient, elegant linear indoor lighting.

? 10W? 960 lm? 180º? IP20

10W
Power960 lm
Luminous flux180º

AngleIP20 / IK08
Protection

The **linear LED batten 10W** is the ideal solution for efficient, discreet indoor lighting. With a length of 60 cm and an aluminium-and-polycarbonate design with a silver finish, it adds a modern, elegant touch to any space. Its high-brightness SMD2835 LED chip provides even, clear light of 960 lumens, with a 180º angle for homogeneous coverage.

Sturdy and impact-resistant (IK08) and IP20-rated for indoors, it allows surface mounting (wall or ceiling), accessories included. Its slim design fits perfectly into offices, shops, corridors and residential spaces, powered at 100-240V.

Why choose this product? **? High efficiency**

960 lumens, SMD2835 chip, 180º angle. **? Slim design**

Aluminium + PC, elegant silver finish. **? IP20 / IK08**

Sturdy, impact-resistant, for indoors. Technical specifications Product typeLinear LED battenPower10WLength60 cmLuminous flux960 lmLED chipHigh-brightness SMD2835Beam angle180ºMaterialAluminium + PCInput voltage100-240VPower factor> 0.90ProtectionIP20 (indoor)Impact resistanceIK08Dimensions600x75x25 mm Advantages

- **960 lm at 10W:** high efficiency.
- **180º angle:** homogeneous coverage.
- **Aluminium + PC:** slim silver design.
- **IP20 / IK08:** sturdy and impact-resistant.
- **100-240V:** simple installation.
- **Indoor:** offices, shops, corridors.

Recommended applications ?**Offices** — efficient linear lighting.?**Shops and showrooms** — even light.?**Corridors and halls** — discreet design.?**Residential spaces** — kitchens, garages. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Fix the batten**
Fix the batten to the wall or ceiling.3**Wire it**
Connect the connection cable (100-240V).4**Check**

Restore power and check the lighting. Frequently asked questions **What is the luminous flux?**

960 lumens at 10W, with an SMD2835 chip. **What is the beam angle?**

180º, for homogeneous coverage. **Is it suitable for outdoors?**
No, it is designed for indoors (IP20). ?

10W
960 lm?

180º
60 cm?

IP20
IK08?

In stock
Fast shipping

Product gallery:


10W
60CM