24W 2400Lm CCT LED downlight panel IP20 Cut-out Ø280mm

Product codes:

Reference: PL-DR24W



Product features:

Power (W): 24
Power source (V): 220-240V
Color temperature CCT: Seleccionable 3000K-4000K-6000K
Brightness (Lm): 2400
Color rendering index (Ra):: ?80
Colour: White
IP: IP20
Luminous angle: 120°
Frequency (Hz): 50-60Hz
Forma: Redondo
Measures (mm): Ø300x13mm
Medida de corte (mm.): Ø280mm
Material: Aluminum + PC
Operating temperature: -20ºC ~ +40ºC
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 25.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K-6000K)

Product description:

Selectable-CCT downlight, opal diffuser Circular Recessed LED Downlight 24W 2400 lm CCT Ø280 mm cut-out

The (2400 lm) in white aluminium with an opal PC diffuser offers soft, glare-free light.
, Ø293x13 mm, Ø280 mm cut-out, external driver, 3-year warranty.

? 24W? 2400 lm? CCT? Ø280 mm

24W

Power2400 lm
Luminous flux120º
BeamØ280 mm
Cut-out

The **24W circular recessed LED downlight** is a modern, efficient lighting solution, ideal for a wide variety of indoor spaces. With an elegant, discreet design, it offers clear, even light thanks to its 2400-lumen flux and a 120º angle.

Made of white aluminium with an **opal polycarbonate diffuser**, it ensures soft, glare-free lighting. Its **colour temperature is selectable (3000K, 4000K or 6000K)** to suit each atmosphere. Dimensions Ø293x13 mm, Ø280 mm cut-out for easy recessed installation. It includes a high-quality external driver, IP20 protection, 3-year warranty.

Why choose this product? **? Selectable CCT**

3000K, 4000K or 6000K to suit the atmosphere. **? Opal diffuser**

Soft, glare-free light, 2400 lm. **? External driver, 3-year warranty**
White aluminium, Ø280 mm cut-out, IP20. Available light shades

Available in three selectable colour temperatures, to match the atmosphere of each space:

3000 K
Warm white4000 K
Neutral white6000 K
Cool white Technical specifications Product typeCircular recessed LED downlightPower24WColour temperatureSelectable CCT 3000K / 4000K / 6000KLuminous flux2400 lmMaterialWhite aluminium + opal PC diffuserDimensionsØ293x13 mm (Ø300 frame)Cut-outØ280 mmBeam angle120ºDriverExternal (included)ProtectionIP20Warranty3 years Advantages

- **Selectable CCT:** 3000K, 4000K or 6000K.
- **Opal diffuser:** glare-free light.
- **2400 lm at 24W:** even lighting.
- **Ø280 mm cut-out:** recessed installation.
- **External driver included:** high quality.
- **3-year warranty:** IP20, indoor use.

Recommended applications ?**Offices and shops** — uniform general lighting.?**Halls and receptions** — comfortable light.? **Hotels and restaurants** — adjustable atmosphere.?**Homes** — false ceilings. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Choose the temperature**
Select 3000K, 4000K or 6000K.3**Prepare cut-out and driver**
Ø280 mm cut-out; wire the external driver.4**Recess and check**

Insert the downlight and check the lighting. Frequently asked questions **Can the temperature be chosen?**

Yes, selectable CCT 3000K, 4000K or 6000K. **What cut-out is needed?**

Ø280 mm (dimensions Ø293x13 mm). **What is the warranty?**
3 years, with external driver included. ?


24W
2400 lm?

CCT
3000-6000K?

Ø280 mm
120º?

Warranty
3 years

Product gallery:


293mm
280mm






Selector CCT 3000K/4000K/6000K