

NEW PRO 30W LED Floodlight OSRAM Chip IP65 3900Lm

Product codes:

Reference: FLOSR30W



Product features:

Power (W): 30
Power source (V): 175-260V
Color temperature CCT: 3000K
Color temperature CCT: 4000K
Color temperature CCT: 6000K
LED: SMD2835
LED chip brand: OSRAM
Luminous efficacy (Lm/W): 130
Brightness (Lm): 3900
CRI: +80
Colour: Grey
IP: IP65
Luminous angle: 110°
Frequency (Hz): 50-60Hz
Power factor: 0.95
Measures (mm): 115x135x31mm
Material: Aluminum + glass
Driver: Flicker-Free integrated driver
Operating temperature: -20°C ~ +55°C
Energy efficiency 2021: A+
Lifespan: 30.000h
Certification: CE - RoHS
Warranty: 5 años

Product attributes:

Color temperature CCT (°K): Cool white 6000K, Natural white 4000K, Warm white 3000K

Product description:

NEW PRO 30W LED Floodlight OSRAM Chip The **30W NEW PRO LED Floodlight** is a powerful and efficient solution for outdoor lighting. With a gray aluminum housing and a frosted glass diffuser to prevent glare, this floodlight provides high-quality illumination with a luminous angle of 110°.

It includes a **OSRAM SMD 2835 LED chip** with high brightness and **130Lm/W** performance, ensuring excellent luminous efficiency. Its compact design with dimensions of 115x135x31mm and an adjustable bracket up to 360° allow for easy mounting on the ground, wall, or ceiling.

It comes with a 15cm connection cable for direct connection to the 220-240V electrical network. Additionally, it features a power factor > 0.95 and an integrated flicker-free LED driver. With **IP65 rating** and CRI>80, it is available in warm white 3000K, neutral white 4000K, and cool white 6000K, with a 5-year warranty.

Technical Specifications

- Power: 30W
- Luminous Flux: 3,900 lm
- Beam Angle: 110°

- LED Chip: OSRAM SMD 2835
- Performance: 130Lm/W
- Dimensions: 115x135x31mm
- Voltage: 220-240V
- Power Factor: > 0.95
- Integrated flicker-free LED driver
- IP Rating: IP65
- CRI: >80
- Color Temperature: Warm White 3000K, Neutral White 4000K, Cool White 6000K
- Warranty: 5 years

Installation Recommendations


It is recommended to install the **30W NEW PRO LED Floodlight** in outdoor areas such as gardens, facades, or sports areas for powerful and uniform illumination. It can be mounted on the ground, wall, or ceiling thanks to its adjustable bracket up to 360°.

Recommended Uses and Applications

This floodlight is ideal for lighting:

- Gardens and outdoor areas.
- Building facades.
- Sports areas such as tennis courts or play areas.
- Shop windows and commercial spaces.

Product gallery:



www.osram-os.com

GWM JTLRSA.EM

DURIS® E 2835

The DURIS® E 2835 combines good efficacy and a wide beam angle into a compact format (2.8 mm x 3.5 mm). This is key to homogeneous illumination applications where the DURIS® E 2835 never fails to impress with its performance on system level.



MAXIMUM PROTECTION- IP65



OSRAM
LEDs
Included



High quality ALUMINIUM housing
with epoxy paint for a long service life.