Empty Tri-Proof Light 120cm IP65 for 2 LED Tubes

Product codes:

Reference: IL-1122



Product features:

Lampholder: G13
IP: IP65
IK: IK08
Measures (mm): 1270x95x60mm
Material: ABS
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Product description:

IP65 waterproof batten for LED tubes Empty IP65 Waterproof Fitting for two tubes 120 cm LED

An waterproof fitting ready to take two tubes of LED tube. In ABS and polycarbonate, with a translucent diffuser and single-end connection, it protects your tubes in damp or dusty environments.

? IP65? 120 cm? G13? ABS + PC

IP65
Protection120 cm
Tube2
No. of tubesG13

Connection

The **IP65 waterproof fitting** is an empty batten prepared for installing **two tubes of 120 cm LED tube**. With an **IP65** protection rating, it effectively protects the tubes against dust and water jets, making it ideal for demanding environments.

Made from **ABS and polycarbonate**, with a grey base and a **translucent diffuser** that lets light through without loss of intensity, it has a compact **1270 x 95 x 60 mm** design. It is supplied pre-wired, with G13 lampholders and single-end connection, and accepts any of our 120 cm LED tubes.

Why choose this product? **? IP65 protection**

Resists dust and water jets. **? Pre-wired G13**

Quick installation with single-end connection. **? ABS and polycarbonate**

Sturdy and durable, with a translucent diffuser and no light loss. Technical specifications Product typeWaterproof fitting for LED tubesProtectionIP65Number of tubes2Compatible tube length120 cmConnectionG13 lampholders, single-endMaterialABS and polycarbonateDiffuserTranslucentDimensions1270 x 95 x 60 mmWiringPre-wired Advantages

- **IP65 sealing:** suited to damp and dusty environments.
- **For two tubes of 120 cm:** compatible with all our LED tubes.
- **Pre-wired G13:** quick single-end installation.
- **ABS and polycarbonate:** sturdy and durable.
- **Translucent diffuser:** light with no loss of intensity.

Recommended applications ?**Garages and workshops** — waterproof technical lighting.?**Warehouses and storage areas** — dusty environments.?**Car parks** — rugged lighting.?**Industrial kitchens and damp rooms** — IP65 protection.
Installation guide 1**Switch off the power**
Cut the supply before installation.2**Fix the fitting**
Fix the fitting to the ceiling or wall using the included brackets.3**Install the tube**
Insert the 120 cm LED tube and seat it on the G13 lampholders.4**Connect and close**

Make the single-end connection, close the fitting and restore power. Frequently asked questions **Which tubes can I use?**

Any of our 120 cm LED tubes with single-end connection. **What is its protection rating?**

IP65: resistant to dust and water jets. **Is it supplied wired?**
Yes, it is pre-wired with G13 lampholders and single-end connection. ?

IP65
Waterproof?

G13
Pre-wired?

ABS + PC
Sturdy?

In stock
Fast shipping

Product gallery:



