

22W 150cm T8 LED Glass Tube OSRAM SMD2835 chip 2860Lm

Product codes:

Reference: IL-TBGOSR22W



Product features:

Power (W): 22
 Power source (V): 220-240V
 Color temperature CCT: 4000K
 Color temperature CCT: 5700K
 LED: SMD2835
 LED chip brand: OSRAM
 Lampholder: G13
 Luminous efficacy (Lm/W): 130
 Brightness (Lm): 2860
 CRI: +80
 Colour: White
 IP: IP20
 Luminous angle: 300°
 Frequency (Hz): 50-60Hz
 Power factor: 0.90
 Measures (mm): Ø26x1500mm
 Material: Glass
 Operating temperature: -20°C ~ +55°C
 Energy efficiency 2021: A+
 Lifespan: 50.000h
 Certification: CE - RoHS
 Warranty: 3 años

Product attributes:

Color temperature CCT (°K): Natural white 4000K, Cool white 5700K

Product description:

22W T8 150cm Glass LED Tube 300° OSRAM Chip 2860Lm Experience exceptional lighting with our 22W T8 LED Tube, featuring high-efficiency OSRAM SMD2835 LED chips. Designed for optimal performance with a light output of 2860 lumens and a wide 300° emission angle, this tube offers options in neutral white 4000K and cool white 5700K to perfectly match your space. Ideal for both residential and commercial environments.

Enhance your lighting with our 22W T8 LED Tube, designed for superior efficiency and long durability. This 150cm tube is equipped with premium OSRAM SMD2835 LED chips, delivering an impressive 130Lm/W efficiency for a total of 2860 lumens. With a 300° light distribution angle and a high Color Rendering Index (CRI) of over 80, it ensures vivid and natural light. Made from durable glass, this LED tube maintains a power factor greater than 0.90, ensuring energy efficiency. It includes an LED Starter fuse and comes with a 3-year warranty, promising over 50,000 hours of bright light. Available in neutral white 4000K and cool white 5700K to meet your needs.

Technical Data:

- **Power:** 22W
- **Luminous Flux:** 2860 lumens
- **LED Chip Type:** OSRAM SMD2835

- **Efficiency:** 130Lm/W
- **Light Angle:** 300°
- **Color Rendering Index (CRI):** >80
- **Power Factor:** >0.90
- **Material:** Glass
- **Dimensions:** Ø26x1500mm
- **Lifespan:** 50,000 hours
- **Warranty:** 3 years
- **Color Temperature:** Available in 4000K (neutral white) and 5700K (cool white)
- **Starter:** Includes LED Starter fuse

Installation Recommendations:

Ensure your installation surface is clean and secure. Since this tube connects at one end, it simplifies wiring and maintenance. When replacing an existing fluorescent tube, ensure that the LED Starter fuse is properly installed to protect against short circuits. Always turn off the power before beginning installation to avoid any electrical hazards.

Recommended Uses and Applications:

This versatile LED tube is perfect for a wide range of applications:

- **Commercial Settings:** Illuminate office spaces, retail locations, and warehouses with clear, bright light.
- **Residential Uses:** Ideal for kitchens, basements, garages, and utility rooms where high-quality light is crucial.
- **Educational Institutions:** Provide well-lit environments for schools and libraries, enhancing both student and staff comfort.
- **Healthcare Facilities:** Utilize in hospitals and clinics to ensure precise and efficient lighting conditions.

Product gallery:

High Lumens



www.osram-os.com

GWM JTLRSA.EM

DURIS® E 2835

The DURIS® E 2835 combines good efficacy and a wide beam angle into a compact format (2.8 mm x 3.5 mm). This is key to homogeneous illumination applications where the DURIS® E 2835 never fails to impress with its performance on system level.



