

10W 1300Lm CCT IP44 PRO LED Downlight LIFUD driver UGR19

Product codes:

Reference: IL-90804



Product features:

Power (W): 10

Power source (V): 220-240V

Color temperature CCT: Seleccionable

3000K-4000K-6000K LED: SMD2835

LED chip brand: EPISTAR Luminous efficacy (Lm/W): 130

Brightness (Lm): 1300

CRI: +85 Colour: White IP: IP44

Luminous angle: 120°
Frequency (Hz): 50-60Hz
Measures (mm): Ø95x35mm
Medida de corte (mm.): Ø88mm
Material: Aluminum + PC
Driver: LIFUD flicker-free

Operating temperature: -20°C ~ +55°C

Energy efficiency 2021: A+ Energy efficiency 2023: E Lifespan: 40.000h Certification: CE - RoHS Warranty: 5 años

Product attributes:

Color temperature CCT (°K): Selectable CCT (3000K-4000K-6000K) Dimming system: No dimming (On/Off), TRIAC, 1-10V, DALI

Product description:

Recessed LED Downlight Round IP44 10W CCT Round recessed LED downlight with 10W power, equipped with a high-performance EPISTAR SMD2835 LED chip, providing a luminous flux of 1300 lumens. It features a microprismatic diffuser with a UGR19 rating, significantly reducing the glare effect of traditional downlights.

The LIFUD driver includes a CCT color temperature selector, allowing you to select the color temperature between 3000K / 4000K / 6000K in a single device.

With an IP44 rating on the panel, it is perfect for installations in bathrooms, kitchens, and humid areas, as well as covered outdoor spaces.

Technical data for the recessed LED downlight IP44 round 10W

Outer dimensions: Ø95x35mm
Ceiling cutout: Ø88mm

• **Depth:** 35mm

• Average consumption: 10W



- Replacement for: 100W conventional luminaires / 26W low consumption luminaires
- Energy consumption savings: 90%
- Includes external driver: with CCT color selector function
- CCT color temperatures: 3000K / 4000K / 6000K
- Driver connection: direct to 230V mains
- Panel ingress protection: IP44, suitable for humid areas. Not recommended for outdoor use.
- Luminous angle: 120°
 Low glare rating: UGR19
 Color rendering: CRI>85

Benefits of the recessed round IP44 10W LED Downlight

- Energy efficiency: With a consumption of 10W, it replaces 100W conventional luminaires, saving up to 90% in energy consumption.
- Color temperature selector: The LIFUD driver allows choosing between 3000K, 4000K, and 6000K in a single device, adapting to the space's needs.
- Resistance and durability: With IP44 ingress protection, it is perfect for bathrooms, kitchens, and humid areas.
- Quality lighting: With a CRI>85 and a 1200 luminous angle, it offers uniform and high-quality light.
- Glare reduction: Thanks to its microprismatic diffuser with UGR19, glare is minimized, providing a visually comfortable environment.

Recommended Uses and Applications

- Bathrooms and kitchens: Ideal for humid areas due to its IP44 protection rating.
- Offices and shops: Perfect for work and sales areas where uniform and glare-free lighting is needed.
- Hallways and common areas: Provides efficient and comfortable lighting in high-traffic areas.
- Covered outdoor areas: Suitable for outdoor use as long as they are covered and protected from direct rain.

Installation Recommendations

- Make the ceiling cutout with a round hole of Ø88mm.
- Connect the external driver directly to the 230V mains.
- Select the desired color temperature using the LIFUD driver CCT selector.
- Insert the downlight into the cutout and secure it firmly.
- Ensure the electrical connection and installation comply with current regulations.

Product gallery:





