

# 30W CCT IP44 PRO LED Square Downlight LIFUD driver UGR19 3600Lm

### **Product codes:**

Reference: IL-90811



### **Product features:**

Power (W): 30

Power source (V): 220-240V

Color temperature CCT: Seleccionable

3000K-4000K-6000K LED: SMD2835

LED chip brand: EPISTAR Luminous efficacy (Lm/W): 120

Brightness (Lm): 3600

CRI: +85 Colour: White IP: IP44

Luminous angle: 120° Frequency (Hz): 50-60Hz

Forma: Cuadrado

Measures (mm): 225x225x35mm Medida de corte (mm.): 205x205mm

Material: Aluminum + PC

Operating temperature: -20°C ~ +55°C

Energy efficiency 2021: A+ Energy efficiency 2023: E Lifespan: 40.000h Certification: CE - RoHS Warranty: 5 años

### **Product attributes:**

## **Product description:**

Square Recessed LED Downlight IP44 30W CCT Square recessed LED downlight of 30W power, with high-performance EPISTAR SMD2835 LED chip, providing a luminous flux of 3600 lumens. It features a micro-textured diffuser with a UGR19 rating, significantly reducing the glare effect of traditional downlights.

The LIFUD driver includes a CCT color temperature selector, allowing you to select the color temperature between 3000K / 4000K / 6000K in a single device.

With an IP44 rating on the panel, it is perfect for installations in bathrooms, kitchens, and humid areas, as well as covered outdoor spaces.

Technical Data of the Square Recessed LED Downlight IP44 30W

Outer dimensions: 225x225mmCeiling cutout: 205x205mm

• Depth: 35mm

• Average consumption: 30W



- Replacement for: 300W in conventional luminaires / 56W in low consumption luminaires
- Energy consumption savings: 90%
- Includes external driver: with CCT color selector function
- CCT color temperatures: 3000K / 4000K / 6000K
- Driver connection: direct to 230V mains
- Panel IP rating: IP44, suitable for humid areas. Not recommended for outdoor use.
- Luminous angle: 120°
  Low glare rating: UGR19
  Color rendering index: CRI>85

### Benefits of the Square Recessed LED Downlight IP44 30W

- Energy efficiency: With a consumption of 30W, it replaces 300W conventional luminaires, saving up to 90% in energy consumption.
- Color temperature selector: The LIFUD driver allows choosing between 3000K, 4000K, and 6000K in a single device, adapting to the needs of the space.
- Resistance and durability: With an IP44 rating, it is perfect for bathrooms, kitchens, and humid areas.
- Quality lighting: With a CRI>85 and a luminous angle of 120°, it offers uniform and high-quality light.
- Glare reduction: Thanks to its microprismatic diffuser with UGR19, glare is minimized, providing a visually comfortable environment.

### Recommended Uses and Applications

- Bathrooms and kitchens: Ideal for humid areas thanks to its IP44 protection rating.
- Offices and shops: Perfect for work and sales areas where uniform and glare-free lighting is needed.
- Corridors and common areas: Provides efficient and comfortable lighting in high-traffic areas.
- Covered outdoor areas: Suitable for outdoor use as long as they are covered and protected from direct rain.

#### Installation Recommendations

- Make the ceiling cutout with a square opening of 205x205mm.
- Connect the external driver directly to the 230V mains.
- Select the desired color temperature using the CCT selector on the LIFUD driver.
- Insert the downlight into the cutout and secure it firmly.
- Ensure that the electrical connection and installation are carried out in accordance with current regulations.

### **Product gallery:**



