40W Recessed Selectable CCT LED Spotlight for High Ceilings IP65 5000Lm

Product codes:

Reference: 90722



Product features:

Power (W): 40
Power source (V): 175-260V
Color temperature CCT: Seleccionable 3000K-4000K-6000K
LED: COB
LED chip brand: BRIDGELUX
Luminous efficacy (Lm/W): 125
Brightness (Lm): 5000
Color rendering index (Ra):: ?85
Colour: White
IP: IP65
Luminous angle: 120º
Frequency (Hz): 50-60Hz
Power factor ?: 0.95
Measures (mm): Ø165x115mm
Medida de corte (mm.): Ø145mm
Material: Aluminum + PC
Driver: Philips CertaDrive
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 40.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K-6000K)

Product description:

Round CCT Recessed LED Spot, microprismatic diffuser UGR13 Recessed LED Spot round 40W CCT 5000 lm UGR13 SMD2835 Chip IP65

The with a SMD2835 chip delivers (120º), with a microprismatic diffuser that reduces glare. Selectable CCT temperature via the included driver, IP65.

? 40W? 5000 lm? UGR 13? CCT

40W
Power5000 lm
Luminous fluxUGR 13
GlareIP65
Protection

The **40W recessed round recessed led spot**, fitted with a high-performance SMD2835 chip, is an efficient, durable lighting solution, perfect for commercial and residential applications. With a 120º angle, it lights any space evenly, without shadows, and provides 5000 lumens. Made of aluminium, its slim, refined design adds a modern touch.

Its **microprismatic diffuser** (UGR 13) significantly reduces glare and eye strain, for comfortable lighting. The **colour temperature is selectable** thanks to the included driver, letting you adapt the atmosphere to each room in a single device. IP65 protection, dust- and water-resistant.

Why choose this product? **? UGR 13, microprismatic diffuser**

Reduces glare, comfortable lighting. **? Selectable CCT**

Adapt the temperature to each room (driver included). **? SMD2835 chip, IP65**
5000 lm, 120º, aluminium. Available light shades

Selectable colour temperature, your choice:

3000 K
Warm white4000 K
Neutral white Technical specifications Product typeRecessed round Recessed LED SpotPower40WLuminous flux5000 lmLED chipSMD2835Beam angle120ºDiffuserMicroprismatic (UGR 13)MaterialAluminiumProtectionIP65DriverIncluded Advantages

- **UGR 13:** microprismatic diffuser.
- **Selectable CCT:** temperature of choice.
- **5000 lm at 40W:** even lighting.
- **SMD2835 chip:** high performance.
- **Driver included:** CCT selector.
- **IP65:** dust and water.

Recommended applications ?**Offices and shops** — comfortable lighting.?**Hotels and restaurants** — adjustable atmosphere.?**Bathrooms and kitchens** — damp areas.?**Homes** — false ceilings. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Choose the temperature**
Set the CCT selector on the driver.3**Wire it**
Wire the included driver to the mains.4**Recess and check**

Insert the luminaire and check the lighting. Frequently asked questions **Can the temperature be chosen?**

Yes, the CCT is selectable via the included driver. **Does it reduce glare?**

Yes, its microprismatic diffuser offers a UGR 13. **Is it suitable for outdoors?**
Yes, in covered outdoors (IP44/IP54/IP65). ?

40W
5000 lm?

UGR13
CCT?

Selectable
SMD2835?

IP65
Driver incl.

Product gallery:


PHILIPS
CertaDrive
LED driver
CCT
3 Colors inside:
3000
4000
6000








Cut: Ø 145 mm
H = 150 mm