8W Selectable CCT Square Nickel Surface LED Ceiling Light OSRAM chip 880Lm

Product codes:

Reference: il-PSD8WB



Product features:

Power (W): 8
Power source (V): 85-265V
Color temperature CCT: Seleccionable 3000K-4000K-6000K
LED: SMD2835
LED chip brand: OSRAM
Luminous efficacy (Lm/W): 110
Brightness (Lm): 880
Color rendering index (Ra):: ?80
Colour: Plata
IP: IP20
Luminous angle: 120º
Frequency (Hz): 50-60Hz
Measures (mm): 120X120x25mm
Material: Aluminum + PC
Operating temperature: -20ºC ~ +55ºC
Energy efficiency 2021: A+
Energy efficiency 2023: F
Lifespan: 40.000h
Certification: CE - RoHS
Warranty: 3 años

Product attributes:

Color temperature CCT (ºK): Selectable CCT (3000K-4000K-6000K)

Product description:

Square surface ceiling light CCT, ceiling or wall Square LED Ceiling Light 8W satin nickel OSRAM SMD2835 Chip 880 lm CCT IP20

The in satin nickel finish with a OSRAM SMD2835 chip delivers . Elegant design, surface mounting on ceiling or wall, IP20. CCT selector (3000K / 4000K / 6000K).

? 8W? 880 lm? CCT? IP20

8W
Power880 lm
Luminous fluxCCT
TemperaturesIP20
Protection

The **8W square surface LED ceiling light**, in satin nickel finish, is an elegant, efficient lamp, perfect for lighting any room. With a luminous flux of 880 lumens thanks to its **OSRAM SMD2835** LED chip known for efficiency and durability, it adds a modern touch to any interior.

It mounts easily **on the surface**, on the ceiling or wall, and includes all the accessories needed for installation. Its CCT selector lets you choose between warm white, neutral white and cool white, to suit any atmosphere. Dimensions 120x120x25 mm.

Why choose this product? **? Selectable CCT**

3000K, 4000K or 6000K to suit the atmosphere. **? OSRAM SMD2835 chip**

880 lm at 8W, high efficiency. **? Surface mounting**
Ceiling or wall, accessories included. Available light shades

Available in three selectable colour temperatures, to match the atmosphere of each space:

3000 K
Warm white4000 K
Neutral white6000 K
Cool white Technical specifications Product typeSquare surface LED ceiling lightPower8WLuminous flux880 lmLED chipOSRAM SMD2835Coloursatin nickelColour temperatureCCT 3000K / 4000K / 6000KDimensions120x120x25 mmProtectionIP20MountingSurface (ceiling or wall) Advantages

- **Selectable CCT:** 3000/4000/6000K.
- **OSRAM SMD2835 chip:** 880 lm at 8W.
- **Surface mounting:** ceiling or wall.
- **Accessories included:** easy installation.
- **Aluminium:** sturdy and durable.

Recommended applications ?**Living rooms and bedrooms** — general lighting.?**Corridors and halls** — surface mounting.?**Shops and offices** — elegant finish.?**Kitchens and dining rooms** — pleasant light. Installation guide 1**Switch off the power**
Cut the supply before installation.2**Choose the temperature**
Set the CCT selector (3000/4000/6000K).3**Surface-mount it**
Fix the ceiling light with the included accessories.4**Wire and check**

Wire to the mains and check the lighting. Frequently asked questions **Can the temperature be chosen?**

Yes, between 3000K, 4000K and 6000K via the CCT selector. **What is the luminous flux?**

880 lumens at 8W (OSRAM SMD2835 chip). **Is it dimmable?**
No, it works on/off. ?

8W
880 lm?

CCT
OSRAM SMD2835?

Surface
IP20?


In stock
Fast shipping

Product gallery:




3 COLOR INSIDE
3000
4000
6000
GWM JTLRSA.EM
DURIS® E 2835
OSRAM


CRI<70
Ra
Chromatic Reproduction Index
Farbwiedergabeindex
Indice de Reproducción Cromática
Rendu des Couleurs
Indice de rendu des couleurs
Indice di resa cromatica
CRI >85


Complete with 1000mA driver.
Dimensions
120x
120mm
25mm
Select color :
Daylight - Cool white - Warm white
3000K 4000K 6000K
85
CRI


Panel Light
switch to
down
light!
OSRAM
LEDs
Included