

## Pack of 2 - 40W IP65 60x60 LED Panel Philips driver 4400Lm

### Product codes:

Reference: PACK2-PHPN40W-IP65



### Product features:

Power (W): 40  
 Power source (V): 175-260V  
 Color temperature CCT: 4000K  
 Color temperature CCT: 5700K  
 LED: SMD2835  
 Luminous efficacy (Lm/W): 110  
 Brightness (Lm): 4400  
 CRI: +80  
 Colour: White  
 IP: IP65  
 Luminous angle: 120°  
 Frequency (Hz): 50-60Hz  
 Power factor: 0.91  
 Measures (mm): 595x595x35mm  
 Material: Aluminum + PC  
 Driver: Philips CertaDrive  
 Operating temperature: -20°C ~ +55°C  
 Energy efficiency 2021: A+  
 Energy efficiency 2023: F  
 Lifespan: 50.000h  
 Certification: CE - RoHS  
 Warranty: 5 años

### Product attributes:

Color temperature CCT (°K): Natural white 4000K, Cool white 5700K

### Product description:

Pack of 2 LED Recessed Panels 60x60cm 40W IP65 The **Pack of 2 LED Recessed Panels** 60x60cm and 40W is an efficient and modern lighting solution, with IP65 classification, ideal for clean rooms and areas with humidity and vapor condensation. With a luminous flux of 4400 lumens and a backlight system, it guarantees clear and uniform lighting. Equipped with a Philips CertaDrive driver for professional use, it offers flicker-free and noise-free lighting.

The **LED Panel** has a 120° luminous angle and a CRI > 80, ensuring excellent color reproduction. Its dimensions are 595x595x35mm, with a greater thickness than slim panels, making them more rigid and robust. They include a 5-year warranty, ensuring their durability and reliability.

#### Technical Specifications

- **Material:** Aluminum and PC
- **Power:** 40W
- **Luminous Flux:** 4400 lumens
- **Backlight System:** Backlight
- **IP Classification:** IP65
- **Panel Dimensions:** 595x595x35mm

- **Luminous Angle:** 120°
- **Power Factor:** > 0.91
- **CRI:** > 80
- **Driver:** Philips CertaDrive
- **Warranty:** 5 years

What is a Backlight Panel?

A **backlight panel** is a type of LED panel that has the light source at the base, allowing for much more uniform and superior light diffusion compared to slim panels. These panels are thicker, more rigid, and robust, offering greater durability. Additionally, they are equipped with a diffuser that does not yellow over time, maintaining the quality of light throughout their lifespan.

Uses and Applications

- **Clean Rooms:** Perfect for areas requiring high cleanliness and contamination control.
- **Areas with Humidity:** Ideal for places with high humidity and vapor condensation.
- **Offices:** Provides clear and uniform lighting, ideal for work environments.
- **Stores:** Enhances product visibility and creates a pleasant atmosphere for customers.
- **Homes:** Perfect for kitchens, living rooms, and other areas requiring good lighting.
- **Hospitals:** Provides clear and constant light, essential in healthcare environments.
- **Schools:** Ensures optimal lighting in classrooms and hallways.

Product gallery:



