30x120cm recessed frame for LED panel in plasterboard

Product codes:

Reference: IL-MARCO-30120

Product features:

Colour: White
IP: IP20
Material: Aluminum
Certification: CE - RoHS
Warranty: 3 años



Product attributes:

Product description:

Flush recessed frame for LED panels Frame to Recess 30x120 cm LED Panel in Plasterboard - White Aluminium

The in white-lacquered aluminium lets you perfectly integrate an LED panel into plasterboard ceilings. Recommended cut-out 35x125 cm, fixing clips included, clean, professional flush finish. Compatible with any 30x120 cm panel (slim or backlight).

? 30x120 cm? Aluminium? Placoplâtre? Affleurant

30x120 cm
Panel format35x125 cm

Cut-outAluminium
WhiteFlush
Finish

The **30x120 cm recessed frame** improves the installation of your LED panels by integrating them into plaster or plasterboard ceilings. Made of white-lacquered aluminium, it ensures perfect integration and a clean, professional finish.

The frame is designed for a **recommended cut-out of 35x125 cm** in the ceiling. It includes **fixing clips** against the plasterboard and is designed to be completely flush with the ceiling. Supplied unassembled (assembly required), it is compatible with any 30x120 cm LED panel model, whether slim or backlit.

Why choose this product? **? Plasterboard recessing**

Perfect integration into plaster ceilings. **? Flush finish**

Clean and professional, clips included. **? 30x120 cm-compatible**
Slim or backlit panels, white-lacquered aluminium. Technical specifications Product typeRecessed frame for LED panelCompatibility30x120 cm LED panels (slim or backlight)MaterialWhite-lacquered aluminiumRecommended cut-out35x125 cmFixingClips against plasterboardFinishFlush with the ceilingDeliveryUnassembled (assembly required) Advantages

- **Plasterboard recessing:** perfect integration.
- **Flush finish:** clean and professional.
- **35x125 cm cut-out:** clips included.
- **White-lacquered aluminium:** sturdy and attractive.
- **30x120 cm-compatible:** slim or backlit.
- **Supplied unassembled:** simple assembly.

Recommended applications ?**Plasterboard ceilings** — panel recessing.?**Offices and shops** — professional finish.?**Renovations** — flush integration.?**Plaster ceilings** — recessed LED panels. Installation guide 1**Assemble the frame**
Assemble the frame (supplied unassembled).2**Prepare the cut-out**
Make a 35x125 cm cut-out in the plasterboard.3**Fix the frame**
Fix the frame with the clips against the plasterboard.4**Fit the panel**

Insert the LED panel and check the flush finish. Frequently asked questions **What is the recommended cut-out?**

35x125 cm in the plasterboard ceiling. **Which panels is it compatible with?**

With any 30x120 cm LED panel, slim or backlit. **Is it supplied assembled?**
No, it is supplied unassembled and requires assembly. ?

Plasterboard
30x120 cm?

Cut-out
35x125 cm?

Aluminium
White?

In stock
Fast shipping

Product gallery:

